

**NEW!**

# easyOUT™

QUICK FIX

## sprinkler removal tool

Underhill®

spray head removal & replacement just got easier and faster!

*Finally, a unique tool designed and engineered to help you do the job like never before...*

- No Digging
- No Damage to Turf
- Saves Time and Money

*Fits All Major **Spray Head** Brands – Removes Sprinkler in 3 Minutes or Less*

**Here is how it works, it's as easy as 1-2-3-4... Done!**

### SPRINKLER REMOVAL & REPLACE

#### STEP 1



- Remove cap and inside components
- Insert rod into sprinkler body

#### STEP 2



- Place tool over rod and inside sprinkler body
- Rotate tool counter clockwise to remove body

#### STEP 3



- Place new sprinkler over rod and into ground
- Push down and rotate tool clockwise to connect sprinkler body to pipe

#### STEP 4



- Replace new sprinkler components and cap



Ultra Heavy-Duty Precision Engineered Material

Two models for:  
2" - 6" Pop-Up Sprinklers  
part# A-E0-SRT12K

2" - 12" Pop-Up Sprinklers  
part# A-E0-SRT18K

Rod prevents dirt from entering pipe and fitting

Underhill®

Products that work... smart™

toll free 1-866-863-3744

web [www.underhill.us](http://www.underhill.us)

X3Mgolf / ExtremeGolf • +45 70202207 • [www.x3mgolf.dk](http://www.x3mgolf.dk)

- No Digging!
- No Damage to Turf!
- Save Time & Save Money!

## The Ultimate All-In-One Device for Repairs/Modifications

### RAISE SPRINKLER • OPTION


It's a snap with **EasyOut™**... Easily increase the spray head height to grade by removing the sprinkler and screw on a standard PVC or Cut-Off fitting to the bottom of the sprinkler. **2 options to choose from.** Add additional PVC fittings to increase height.



### CAP-OFF SPRINKLER • OPTION

**EasyCap™** makes plugging off any unwanted sprinklers super easy & fast... A BIG labor savings.

Remove spray head and insert the **EasyCap™** fitting (part # A-EO-05EC) to the bottom of the **EasyOut™** tool and screw in the **EasyCap™** fitting...that's it!



### DRIP CONVERSION • OPTION


Converting spray heads to drip using EasyOut™ tool is simple and fast.

#### STEP 1



Remove existing sprinkler

#### STEP 2



Attach drip tubing to 7mm barb drip fitting

#### STEP 3



Pass drip tubing through tool, Attach drip fitting to Hex on tool, Screw drip fitting/tubing to pipe



#### ordering

##### Part #:

A-EO-SRT12K	EasyOut™ fits 2" - 6" spray heads
A-EO-SRT18K	EasyOut™ fits 2" - 12" spray heads
A-EO-05EC	EasyCap™ ½" female FPT fitting



#### Underhill International Corporation

25782 Obrero Dr., Unit C • Mission Viejo, CA 92691  
 tel: 949.305.7050 • fax: 949.305.7051  
 toll-free: 866.863.3744 • www.underhill.us

© 2015 Underhill International Corporation. All rights reserved.  
 This literature is for informational purposes only. Underhill International makes no warranties, expressed or implied, in the product descriptions.



Form # UE0-A16

Products that work... smart™